



## ECM-270

Order No.: 0235140

### PRODUCTINFOS

#### **Professional condenser microphone,**

for studio applications and live performances. Ideally suited for direct or overhead sound pickup of acoustic instruments and vocals.

- Back electret cardridge with cardioid polar pattern
- Low cut switch
- Selectable 10 dB attenuation
- Electronically balanced output
- Robust brass body of high quality
- Supplied accessories: robust hard-sided case, microphone windshield, microphone support (spider) for 16 mm ( $\frac{5}{8}$ " stand

### TECHNICAL SPECIFICATIONS

#### **ECM-270**

Description	electret microphone
Transmission method	cable

**ECM-270**

Polar pattern	cardioid
System	back electret
Audio frequency range	50-18,000 Hz
Nominal impedance	200 $\Omega$
Sensitivity	5.6 mV/Pa
S/N ratio	> 60 dB
Max. sound pressure	135 dB
Power supply	DC 48 V, phantom power
Housing material	brass
Admiss. ambient temp.	0-40 °C
Dimensions	Ø 20 mm x 150 mm
Weight	140 g
Connection	XLR, bal.
Packing dimensions (W x H x L)	0.285 x 0.08 x 0.22 m
Gross weight	0.621 kg
Net weight	0.191 kg